

LOW-VOLTAGE RESIDENTIAL BATTERY

BLF SERIES BATTERY: BLF-12100/12200/12280/24100

BLF series Li-ion Battery is a reliable and cost-effective energy storage solution. With its high-quality materials and advanced manufacturing process, BLF series offers high energy density, long cycle life, and excellent performance, and it also guarantees safety, efficiency, and environmental friendliness.

Safe & Flexible to Use

- Operating within a widely temperature range of -20 to 55 degrees.
- Deep cycles, automatically cut off power when reaching the cut-off voltage.

Long-lasting Endurance

- Supports up to 6000 charge-discharge cycles.
- Supports 4-series boosting to form a 51.2V system.

User Friendly

- Compatible with all off-grid inverters and hybrid inverters on the market (requiring such inverters to support the lithium battery working mode).
- Low price: with costs essentially on par with those of lead-acid batteries of the same level
- Lightweight - 1/3 the weight of lead-acid batteries of the same capacity

Modular Expansion

- Maximum support for 4-series and 4-parallel expansion, reaching a
- total capacity of 40kWh



LOW-VOLTAGE RESIDENTIAL BATTERY

BLF SERIES BATTERY:BLF-12100/12200/12280/24100

BATTERY

Model	BLF-12100	BLF-12200	BLF-12280	BLF-24100
Cell Type	LFP			
Nominal Voltage(V)	12.8	12.8	12.8	25.6
Operating Voltage Range(V)	10.0 - 14.4	10 - 14.4	10 - 14.4	20.0 - 28.8
Rate Capacity(Ah)	100	200	280	100
Total Energy(kWh)	1.28	2.56	3.584	2.6
Rated Charge Discharge Current(A)	50 / 50	50 / 100	100 / 100	50 / 50
Max Charge Discharge Current(A)	100 / 100	100 / 200	140 / 200	100 / 100
Depth of Discharge	100%			
Operating Temperature (°C)	Charge: 0°C - 55°C			
Operating Humidity	5% - 95%			
Operating Altitude	< 4000m			
Cooling Type	Natural			
Protection Rating	IP65			
Terminal	M8 * 16			
Cycle Life	6000 Cycles ¹			
Dimensions(W*H*D mm)	333*223.7*175.5	521.5*220.8*238	521.5*220.8*238	521.5*220.8*238
Weight(kg)	10	20	24	20

[1]: Test conditions: 0.5C Charge/0.5C Discharge, @25°C, 90% DOD, 70% EOL.